



BLOCK-DOOR : FIRE RATED 30MIN



-BS NORM-

RANGE	HINGED – DOUBLE ACTION
N° LEAF	SINGLE – DOUBLE – DOOR WITH EXTRA SMALL LEAF
TRANSOM (OVERHEAD)	ON REQUEST
MODEL	ZEN PRO/ IRIS PRO / IRIS DUO PRO / MENARA PRO/ MENARA DUO PRO / LASER PRO / NATURA PRO
DECOR	DEPEND ON THE MODEL
OPENING DIRECTION	LEFT / RIGHT / DOUBLE ACTION
FINISHING	MELAMINE / LAMINATED / WOOD VENEER
CORE	FIRE RATED SOLID CORE
HEIGHT OF PANEL	TILL 2700mm
WIDHT OF PANEL	TILL 1100mm
THICKNESS OF PANEL	44mm FOR WOOD VENEER FINISHING AND 50mm FOR MELAMINE AND LAMINATED
EDGES OF THE PANEL	SQUARE
HEIGHT OVERALL	HEIGHT OF PANEL + 40mm
WIDTH OVERALL	WIDTH OF PANEL + 68mm
FRAME SECTION	FROM L 70 X L 47mm TILL L 150 X L 47mm
FRAME MATERIAL	MDF – HARDWOOD – METAL
INTUMESCENT SEAL	PALUSOL 15 X 4mm APPLY ON THE 4 EDGES OF THE PANEL
HEIGHT ADJUSTABLE	NOT ALLOWED
HINGES	FIRE RATED HINGES
LOCK	FIRE RATED LOCK
HANDLE	ON REQUEST
PACKAGING	SHRINK WRAP FILM + CARDBOARD CORNERS + POLYSTYRENE
VOC EMISSIONS	A+
NORM CERTIFICATION	BS 476
OTHER CERTIFICATION	ISO 9001:2015
DIMENSION AND WEIGHT OF PANEL	2040x830 = 50 KG
WARRANTY	1 YEAR